



1) see remarks



Basic features

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Inductive sensor

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M8x1-Male, 3-pin
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1 μ F
Min. operating current I _m	0 mA
No-load current I _o max., damped	10 mA
No-load current I _o max., undamped	8 mA
Operating voltage U _b	10...30 VDC
Output resistance R _a	33.0 kOhm + 2D
Rated insulation voltage U _i	75 V DC
Rated operating current I _e	200 mA
Rated operating voltage U _e DC	24 V
Rated short circuit current	100 A
Ready delay t _v max.	10 ms
Residual current I _r max.	10 μ A
Ripple max. (% of U _e)	15 %
Switching frequency	700 Hz
Utilization category	DC-13
Voltage drop static max.	2.8 V

Environmental conditions

Ambient temperature	0...60 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g _n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP65

Functional safety

MTTF (40 °C)	355 a
--------------	-------

Interface

Switching output PNP normally open (NO)

Material

Housing material Brass, nickel-plated

Material sensing surface PBT

Mechanical data

Dimension Ø 6.5 x 59 mm

Installation quasi-flush

Mounting length 50.00 mm

Size D6.5

Range/Distance

Assured operating distance Sa 2.9 mm

Hysteresis H max. (% of Sr) 15.0 %

Rated operating distance Sn 4 mm

Real switching distance sr 4 mm

Repeat accuracy max. (% of Sr) 5.0 %

Switching distance marking ████

Temperature drift max. (% of Sr) 20 %

Tolerance Sr ±10 %

Remarks

1) Do not clamp in this area.

EMC: EMC protection circuit required, see 825345. Burst: 1.2 IVW: 2.2

The sensor is functional again after the overload has been eliminated.

1) Do not clamp in this area.

Quasi-flushed: See installation instructions for inductive sensors with extended range 825356.

Quasi-flushed: See installation instructions for inductive sensors with extended range 825356.

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

